

Protecta Film Hard Surface



PROTECTA®

Important Information & Precautions Sheet



Main Application:

Self adhesive protection films are designed for temporary protection on surfaces against dirt, scratches and tool marks. They are not designed for protection against corrosion, humidity or chemicals. Their applications are very diverse and the conditions of use can vary from one enterprise to another. For this reason it is essential that the client tests the product to determine the suitability of any film for the intended application.

The evaluation test must take into account the type of material on which the product is used, the surface finish, the temperature and processing constraints, and the time and condition of exterior exposure.

The manufacturer or seller cannot be held responsible for misuse of the product, nor for consequences resulting from surface properties and conditions, or for any problem or issue arising from any use of the film.

Warning:

Always check the label inside of the roll for correct product before use (Protecta Film Hard Surface).

Conditions of Use[^]:

- Do not use Protecta Film Hard Surface on windows (use our Protecta Film Window for this application).
- Not to be used over floors that are still drying or curing.
- Not recommended for use on polished timber or painted floor surfaces.
- Not to be used in conjunction with under floor heating.
- Recommended for up to 60 days use only. Must be removed within 60 days.
- Not to be stored or used in temperatures above 38°C.
- Film must be used within 10 months of manufacture date.
- Please retain this label.

Scan to view this product online



[^] Disclaimer: All specifications pertain to specific manufacturing guidelines and need to be considered in context for the intended application & user interpretation.