

Protecta Film Stone



PROTECTA®



Important Information & Precautions sheet

Main Application:

Self adhesive protection films are designed for temporary protection on surfaces against dirt, scratches and tool marks. They are not designed for protection against corrosion, humidity or chemicals. Their applications are very diverse and the conditions of use can vary from one enterprise to another. For this reason it is essential that the client tests the product to determine the suitability of any film for the intended application.

The evaluation test must take into account the type of material on which the product is used, the surface finish, the temperature and processing constraints, and the time and condition of exterior exposure.

The manufacturer or seller cannot be held responsible for misuse of the product, nor for consequences resulting from surface properties and conditions, or for any problem or issue arising from any use of the film.

Warning:

Always check the label inside of the roll for correct product before use (Protecta Stone Film).

Conditions of Use[^]:

- UV Resistant for 90 days.
- Do not use Hard Surface Protection on windows (use our Window Protection Film for this application).
- Not to be used over floors that are still drying or curing.
- Not recommended for use on polished timber or painted floor surfaces.
- Not to be used in conjunction with under floor heating.
- Recommended for up to 90 days use only. Must be removed within 90 days.
- Not to be stored or used in temperatures above 38°C.
- *Film must be used within 3 months of purchase.*
- *Please retain this label.*

Scan to view this product online



[^] Disclaimer: All specifications pertain to specific manufacturing guidelines and need to be considered in context for the intended application & user interpretation.